

Nano Breathing Air B1-Series NBM 960

- * Free standing absorber
- * Floor or wall mounted
- * Requires no power
- * Easy to replace catalyst purifier cartridges
- * 2 years warranty



| | | | |
|--|------------------------|-----------------|--|
| Operating pressure | bar | Max 12 | |
| Recommended operating temperature | Celcius | 1.5 - 30 | |
| Inlet quality requirements ²⁾ | Particulate size | 0.5 micron | |
| | Min pressure dew point | -40° C pdp | |
| | Max oil content | 0.05 mg/m3 | |
| Outlet rated flow ¹⁾ | Nm3/hour | 1.600 | |
| Inlet & Outlet connection | NPT (f) | 2 1/2" | |
| Dimensions HxWxD | MM | 400 x 910 x 870 | |
| Weight | Kg | 180 | |

- service guidelines*
- M1 and M01 coalescing filter elements should be changed every year
 - AC elements should be changed every 1000 hours, or 6 months, whichever is sooner
 - purification cartridges have an estimated life of 12000 hours, or 2 years, whichever is sooner ⁽³⁾
 - control valves should be changed every 4 years
 - refer to user guide for full service details

- ¹⁾ At inlet conditions of 7 barg and 35° C and 35° C ambient temperature.
For all other operating conditions please contact our Sales Department.
- ²⁾ If the air does not meet these conditions please contact our Sales Department to confirm the additional treatment required.