

Nano Breathing Air B1-Series NBA 3120

- * Breathing Air BS EN 12021:2014
- * Medicinal Air European Pharmacopoeia 5.0 - Monograph 01/2005: 1238 (corrected)
- * Including energy saving outlet dew point control & display ¹⁾
- * Reliable and cost effective design
- * 2 years warranty



| | | | |
|-----------------------------------|-----------|------------------------------|--|
| Voltage | V | 100 to 240v AC | |
| Frequency | Hz | 50 or 60hz | |
| | | | |
| Operating pressure | bar | Min 6 – Max 10 ²⁾ | |
| Recommended operating temperature | Celcius | 1.5 - 35 | |
| | | | |
| Recommended air inlet quality | ISO Class | 3 | |
| Inlet & Outlet connection | BSPP | 2" | |
| Inlet flow | Nm3/hour | 550 | |
| Outlet flow | Nm3/hour | 413 | |
| | | | |
| Dimensions HxWxD | MM | 1473 x 305 x 787 | |
| Weight | Kg | 272 | |

Service Guidelines: Replacement NBA cartridge service kits & replacement of exhaust silencer should take place after 12.000 working hours or 2 years (whatever comes first)

Contact our Sales Department for prices and lead times

¹⁾ Also deliverable without dew point control & display (contact our Sales Department)

²⁾ Contact our Sales Department for higher pressures or flows